

30 / 15 TON **SUPER DUTY**2 STAGE AIR / HYDRAULIC AXLE JACK



Model 545SD

- The extra light weight and portability makes this the ideal service jack for Service Vehicles
- 2 Stages and Lifting Capacities of 30 and 15 Ton make this a very versatile jack.
- The extra long removable handle and rugged rear wheels make for easy positioning of this jack in hard to reach places.
- An integral Descent Metering Valve maintains a controlled and safe lowering of the load
- The piston head seal design is borrowed from Industrial technology providing a superior low and high pressure seal, giving this jack a much better hold under severe load conditions
- Double polished chromed pistons allow for much tighter tolerances which reduces oil bypassing and reduced ram scoring
- Air assisted lowering speeds up ram retraction
- · Built in overload safety valve prevents damage to unit due to excessive load
- Comes with 2 extensions (75mm/3" + 45 mm1.75") and saddle adapter
- Units are tested to -13F(-25C) and +113F(+45C) as well as off center loading to ensure a long life under even the harshest conditions

Specifications:

30 Ton (1st Stage)

• Low Height: 150 MM (5.92")

• High Height: 224 MM (8.82")

• Lift - 74 MM (2.91")

15 Ton (2nd Stage)

• Low Height: 150 MM (5.92")

• High Height: 292 MM (11.5")

• Lift - 142 MM (5.59")

• Working Air Pressure 0.8 to 1.0 Mpa (116 to 145 psi)

• Net Weight: 30 kgs (66 lbs.)

Shipping Weight: 35 kgs. (77 lbs.)

RELATED PRODUCTS



Model 546SD 25/10 Ton 2 Stage



Model 547SD 50/25 Ton 2 Stage



Model 548SD 60/40/20 Ton 3 Stage



Model 549SD 80/50 Ton 2 Stage