

# 50 / 25 TON **SUPER DUTY**2 STAGE AIR / HYDRAULIC AXLE JACK



#### Model 547SD

- SUPER HEAVY DUTY, 2 Stage 50 Ton and 25 Ton built tough for the rigors of the Heavy Duty Trucking, Agricultural and Fleet business
- The piston head seal design is borrowed from Industrial technology providing a superior low and high pressure seal, giving this jack a much better hold under severe load conditions
- The extra long 138cm (54") handle can be locked in 3 positions for easy positioning of this jack in hard to reach places.
- An integral Descent Metering Valve maintains a controlled and safe lowering of the load
- Single piece base construction provides superior strength for increased load stability
- Double polished chromed pistons allow for much tighter tolerances which reduce oil bypassing and reduced ram scoring
- · Air assisted lowering speeds up ram retraction
- Built in overload safety valve prevents damage to unit due to excessive load
- Comes with 2 extensions (75mm/3" + 45 mm1.75") and saddle adapter
- Units are tested to -13F(-25C) and +113F(+45C) as well as off center loading to ensure a long life under even the harshest conditions

### **Specifications:**

50 Ton (1st Stage)

• Low Height: 215 MM (8.46")

• High Height: 332 MM (13.07")

• Lift - 117 MM (4.61")

25 Ton (2nd Stage)

• Low Height: 215 MM (8.46")

• High Height: 446 MM (17.56")

• Lift - 231 MM (9.09")

• Working Air Pressure 0.8 to 1.2 Mpa (116 to 174 psi)

• Net Weight: 73 kgs (161 lbs.)

• Shipping Weight: 75 kgs. (165 lbs.)

## **RELATED PRODUCTS**



**Model 545SD** 30/15 Ton 2 Stage



Model 546SD 25/10 Ton 2 Stage



**Model 548SD** 60/40/20 Ton 3 Stage



**Model 549SD** 80/50 Ton 2 Stage