



## TWO POST LIFT

### SPECIFICATIONS

| Model  | OHX-10                         | OHX-10H                        |
|--|--------------------------------|--------------------------------|
| Lifting Capacity                             | 10,000 lbs                     | 10,000 lbs                     |
| Lifting Time                                 | 57s                            | 63s                            |
| Max. Lifting height: (w/o extension adapter) | 71 15/32"                      | 78 3/4"                        |
| Max. Lifting height: (w/ extension adapter)  | 80 15/32"                      | 87 3/4"                        |
| Max. lock height: (w/o extension adapter)    | 69 5/8"                        | 77 3/16"                       |
| Max. lock height: (w/ extension adapter)     | 78 5/8"                        | 86 3/16"                       |
| Overall Height:(low setting)                 | 144"                           | 168"                           |
| Overall Height:(high setting)                | /                              | 157"                           |
| Overall Width                                | C 135 11/32"~141 1/4"          | C 135 11/32"~141 1/4"          |
| Drive-Thru Clearance                         | D 100 3/16"~106 3/32"          | D 100 3/16"~106 3/32"          |
| Width Between Columns                        | E 112 19/32"~118 1/2"          | E 112 19/32"~118 1/2"          |
| Minimum Pad Height                           | F 3 3/8"                       | F 3 3/8"                       |
| Gross Weight                                 | 1,612 lbs                      | 1,739 lbs                      |
| Motor  | 2.0HP, 220V 60Hz, single phase | 2.0HP, 220V 60Hz, single phase |



OHX-10



OHX-10H

**AMGO**® Hydraulics  
The Manufacturing Powerhouse

OHX-10  
OHX-10H

### TWO POST

## SUPER ASYMMETRIC LIFT

**AMGO OHX-10 OHX-10H** is well known for its excellent performance in elaborately structure. With extremely long carriages, direct drive cylinders and advance features.



**AMGO HYDRAULIC CORPORATION**  
SC Division: 1931 Joe Rogers Jr Blvd, Manning, SC 29102, USA  
Tel:(803)505-6410

TX Division: 4310 Adler, Suite 200, Dallas, TX 75211, USA  
Tel:(214)377-7742

**AMGO**® Hydraulics  
We're More Than a Manufacturer. We Are the Leader in Quality, Service and Support.  
[www.amgohyd.com](http://www.amgohyd.com)

**AMGO**® Hydraulics

### TWO-POST

## SUPER ASYMMETRIC LIFT

**The professional lifts model OHX Series are designed with asymmetric arms but also can be configured with symmetric, Height & Width adjustment, fitting for low ceiling height (model OHX-10) and hight ceiling but with extremely high lifting (model OHX-10H).**

- ✓ 10,000 lbs capacity.
- ✓ Dual hydraulic cylinders, designed and made on high standard, high quality seals.
- ✓ **SuperAsymmetric** allow to load different vehicles in an asymmetric or symmetric configuration.
- ✓ 3/8" aircraft quality cable is used for synchronization.
- ✓ Self-lubricating UHMW Polyethylene sliders and bronze bush.
- ✓ Single-point safety release, and dual safety design.
- ✓ Clearfloor design, provide unobstructed floor space.
- ✓ Overhead safety stop device.
- ✓ Automatic arm restraints keep the arms locked in their proper positions.
- ✓ Adjustable heights for OHX-10H.
- ✓ Stackable adapters 1.5", 2.5", 5" as standard.
- ✓ Detachable foot guard and tool tray.

### FEATURES



• Single point safety release makes it easier for operators to unlock both columns from one column.

• The top beam is designed with adjustment to fit different width demand. Overhead safety shut-off device prevents vehicle damages.

• The stackable rubber pads assembly with 1.5", 2.5", 5" extension adapters.

• Optional Width Extension Kits With these kits the width between posts is adjusted from 112-193/32" to 118-1/2".  
Kits No.: 21004(OHX-10)  
Kits No.: 21005(OHX-10H)

• Optional Saddle adaptors  
Perfect choice for wide size SUV vehicles and light trucks.  
Kits No.: 20802.

### ASYMMETRIC DESIGN ARMS, OPEN-DOOR CLEARANCE

The OHX series lift features our innovative super asymmetric technology providing the versatility to lift vehicles both symmetrically and asymmetrically upon demand.

The warranty time of the lifts:  
5 years for steel construction,  
3 years for hydraulic parts,  
2 years for electrical components.