

CEMB[®] USA

SM645HP2

Professional quality automatic locking tilt-column tire changer with drop center press arm and tire lift helper, highly recommended to easily aid in the servicing of high performance and run flat tires with stiff sidewalls and difficult wheels with deep drop centers. Features dual table clamping cylinders with Space-Saver under table adjustable clamping range.

www.cemb-usa.com



PROUDLY DISTRIBUTED BY



SM645HP2



Automatic Tilt-Back

mount-dismount arm automatically rotates and lowers into position. Utilizes pneumatic control and high quality locking system with roller guides.

Table Top Clamping

Is self-centering with rim diameter index guides to aid in simple external rim clamping avoiding tire and rim scratches.

High Torque Motor

Heavy-duty 110V motor, handles the difficult sidewall tires and deep drop center rims.

HP2 Side Presser

Allows for easy operation on RUN-FLAT and UHP tires up to 26".

Two Stage Inflation


Utilizes bead sealing jets optimized by placement at the clamping jaws. Includes safety limiter.

Bead Breaker Shovel

Foot operated side mounted bead breaker shovel combines speed with power for everyday wheel applications to save time.



DIMENSIONS



Power Supply:	110V, 1ph, 50/60 Hz
Air Pressure:	115-145 psi (8-10 bar)
Rim Diameter (Ext.):	12" - 26"
Tire Diameter:	44" (1118 mm)
Max. Wheel Width:	13" (330 mm)
Turn Table Speed:	8-15 rpm
Shipping Weight:	950 lbs (476 Kg)

CONTACT

CEMB[®] USA

CEMB USA - BL Systems Inc.
2873 Ramsey Road, Gainesville, GA 30501
(678) 717-1050 - sales@cemb-usa.com
www.cemb-usa.com

WWW.CEMB-USA.COM

Because of continuing technological advancements, specifications, models and options are subject to change without notice.