

12K HD 2-POST LE12-3S

Challenger Lifts LE12-3S is the ideal economic 2-post lift for servicing trucks and other vehicles up to 12,000 lbs. Heavy-duty 3-stage front and 3-stage rear arms offer increased versatility, allowing users to safely lift a significantly broader range of modern vehicles, including EVs and delivery trucks with wider OEM-required pickup points.

REQUIREMENTS

-  **14' MINIMUM**
-  **14' RECOMMENDED**
-  **24' RECOMMENDED**
-  **208-230V, 1PH, 20A**

SPECIFICATIONS

MODEL NUMBER	LE12-3S
Lifting Capacity	12,000 lbs.
Rise Height	6' 5¾"
Overall Height	13' 10" / 14' 7"
Overall Width	11' 7¾"
Drive Thru Clearance	8' 7"
Floor to Overhead Switch	13' 3½" / 14' ½"
Front Arm Reach	Min 27½" Max 54½"
Rear Arm Reach	Min 27½" Max 54½"
Screw Pad Height	Min 5¼" Max 6¾"
Rise Time	61s
Required Ceiling Height	13' 11" / 14' 8"
Height Extension	Part # E12EH2 +2' Extension
ALI Certified	☒



CONCRETE SPECS

4" thick, reinforced, free from cracks & seams, rated at 3500+ psi & cured minimum of 28 days

SERVICE BAY LAYOUT

