



FORWARDLIFT

MOBILE COLUMN LIFTING SYSTEMS

The **POWER** and **MOBILITY** to make repairs anywhere in your shop!

HEAVY DUTY

PRODUCTIVITY AND PERFORMANCE FEATURES

Two, four, six or eight column configurations accommodate up to 144,000 lbs.

Battery operated DC power with 110V on-board charger

- Fully hydraulic with protected piston rods
- Locks in each column
- Retractable cord reels (FCH18) with quick connect cables
- Automatic steering / braking system
- Adjustable lifting forks
- Models available with and without batteries



E-STOP Button

PATENTED CONTROL SYSTEM OFFERS:

- Controls for FCH13 and FCH18 columns
- Position memory to configure repeatable lifting cycles
- Visual confirmation of each column's status
- Level lifting within 3" at each column
- Oversized "E-Stop" emergency stop button
- Audible descent alarm for added safety
- Programmable height limiter
- Battery indicator

LIFT OPTIONS:

- High efficiency LED light kit
- Weight gauge
- Large wheel riser kit
- Jack stands
- Frame-engaging fore / aft lift kits

SPECIFICATIONS	FCH218	FCH418	FCH618
Column configuration	2*	4	6
18,000 lb. Capacity	36,000 lbs. (16329kg)	72,000 lbs. (32658kg)	108,000 lbs. (48987kg)
SPECIFICATIONS	FCH213	FCH413	FCH613
Column configuration	2*	4	6
13,000 lb. Capacity	26,000 lbs. (11793kg)	52,000 lbs. (23587kg)	78,000 lbs. (35380kg)
Rise	FCH18 - 70" (1778mm) FCH13 - 69" (1760mm)		
Column width	FCH18 - 45-1/2" (1156mm) FCH13 - 43" (1092mm)		
Wheel rim size	9" to 25" (228 to 610mm)		
Clearance Fork to Column	10" (254mm)		
Rise Time	FCH18 - 78 seconds FCH13 - 68 seconds		
Charging Voltage	110v charger 2.5 amps		

FCH13

13,000 lbs. Column Capacities

#FCH213U100RDYL



FCH18

18,000 lbs. Column Capacities

#FCH218U200RDDs



Forward Lifts meet the highest industry safety and performance standards. Your assurance of certification is the gold ALI/ETL certified label.



www.forwardlift.com

996 Industrial Drive
Madison, IN 47250



Phone: 800.423.1722
Fax: 812.273.7329

