## 10 HP Open Rotary Screw

## **Basic Compressor Features**

- Airend manufactured with German rotary screw components
- Air/oil cooler
- ASME Powder coated air receiver
- Easy to read and access gauges
- Easy to remove bolt on oil cooler for cleaning
- Extended oil drain with ball valve for easy service
- Factory filled with premium synthetic fluid
- Heavy-duty air filter
- Omega profile rotors
- Operating pressures from 100-190 psi available
- Simplified operating controls, no complicated micro-processor
- Single control solenoid operation
- Spin-on oil filter
- TEFC drive motor (3 phase only)
- UL control components

## **Platinum Compressor Features**

- All basic features
- Automatic tank drain
- SMART contact controls
- Vibration isolation pads
- Tank discharge ball valve
- Freight pre-paid in the 48 states & southern Canada

78 dba 37 cfm @ 125 psi 35 cfm @ 150 psi

75 dba 40 cfm @ 125 psi 38 cfm @ 150 psi



Model Number	Phase	Voltage	Tank	Length	Width	Height	Amp Draw 230 Volt	Amp Draw 480 Volt	
R101V80	1	208-230	80 Gallon Vertical	32	24	76	44	N/A	
R103V80	3	208-230-460	80 Gallon Vertical	32	24	76	28	14	
R101H80	1	208-230	80 Gallon Horizontal	60	24	45	44	N/A	
R103H80	3	208-230-460	80 Gallon Horizontal	60	24	45	28	14	
Add -P to model number to make Platinum model									

No Start Up Kit Required Optional 5-year Pump Warranty Available

## **Industrial Gold**

**Quality Air Compressors at a Great Price.** 





