

Automotive & Commercial Filter Crushers 9" & 16" Chambers

The AFC-9 and CFC-16 heavy duty Quickpack® spin-on oil filter crushers feature 100% air operation, providing long lasting maintenance free operation and a significant cost-savings over more expensive electric powered units.

FEATURES:

- Accommodates up to 4 automotive spin-on oil filters simultaneously
- Interlocking feature prevents door from opening until the ram is fully retracted
- Removable catch basin allows crusher to be cleaned periodically
- 100% air operated
- Mounting stand included – no complicated set-up or installation required



485 80081 00

AFC-9 Automotive Filter Crusher – 9" Chamber

485 80082 00

CFC-16 Commercial Vehicle Filter Crusher – 16" Chamber

FEATURE COMPARISON

	AFC-9	CFC-16
Dimensions (H x W x D)	69.5 in x 15 in x 16.8 in (177 cm x 38 cm x 43 cm)	85.5 in x 20.5 in x 16.8 in (217 cm x 52 cm x 43 cm)
Stand Dimensions (H x W x D)	57 in x 29 in x 23 in (145 cm x 74 cm x 58 cm)	61 in x 29 in x 27 in (155 cm x 74 cm x 69 cm)
Shipping Weight	242 lb (110 kg)	282 lb (128 kg)
Crushing Chamber		
Dimensions (H x W x D)	9 in x 8 in x 8 in (23 cm x 20 cm x 20 cm)	16.3 in x 10 in x 8 in (41 cm x 25 cm x 20 cm)
Air Inlet	1/4 female npt	1/4 female npt
Air Pressure	100 to 160 psi (6.9 to 11.0 bar)	100 to 200 psi (6.9 to 13.8 bar)
Catch Basin Connection	3/4 female npt	3/4 female npt
Crushing Force by Air Pressure		
Crushing Force	Air Pressure Required	Air Pressure Required
12,000 lb/6 tons	112 psi (7.7 bar)	112 psi (7.7 bar)
14,000 lb/7 tons	129 psi (8.9 bar)	129 psi (8.9 bar)
16,000 lb/8 tons	147 psi (10.1 bar)	147 psi (10.1 bar)
18,000 lb/9 tons	165 psi (11.4 bar)	165 psi (11.4 bar)
20,000 lb/10 tons	183 psi (12.6 bar)	183 psi (12.6 bar)
22,000 lb/11 tons	200 psi (13.8 bar)	200 psi (13.8 bar)