

R1090

PRO 3D ALIGNMENT SYSTEM

HIGH PERFORMANCE SYSTEM WITH SOLID VISION TECHNOLOGY

Equipped with fixed cameras, tire grabbing clamps and remote controlled sensors.

- Automatic positioning of the cameras
- Automatic recognition of the targets
- ADAS ready

3D CAMERAS COMMUNICATE VIA BLUETOOTH

No cables or interruptions during alignment process.

AUTOMATIC LIFT LEVEL COMPENSATION

This innovative wireless system can be used on a number of service of lifts thanks to its automatic flatness compensation.

AUTOMATIC CAMERA POSITIONING - ALIGNMENT READINGS IN SECONDS

No adapters required while obtaining caster readings

NO MINIMUM BAY SIZE REQUIRED

Wireless capability with the mobility to move from bay to bay

FAST AND EASY SET UP

with Console or Tablet Operated System

- Includes Android Tablet as a REMOTE indicator

Easy to follow alignment process with updated graphics that feature a time saving

On Rack Test Drive Program

- Animated instructions
- Easy to read results
- Adjustment Illustrations
- Live adjustments
- Email or print alignment report

Handheld tablet allows techs to read and make adjustments anywhere in the bay!

PRECISION TARGET READING HIGH RESOLUTION FIXED CAMERAS

New smaller, rubber armored, wireless measuring heads with digital display keyboard with remote-control function



SINGLE SENSOR SUPPORT PROVIDES HEAD POSITION ON RUNWAYS FOR MULTIPLE VEHICLE WHEELBASES

Quick clamp to the lift, this pivoting support avoids damage with obstacles while lowering.



Requires a single head position to measure different wheel base vehicles.



Large 32" HD Monitor



New portable cabinet with increased storage.

Compact size for workshops with limited space.



EXCLUSIVE 3DT® TARGETS with Solid Vision Technology

EXTREMELY FAST

NO ROLL-BACK COMPENSATION REQUIRED FOR MOST VEHICLES

- Extremely light
- No electronic components inside
- Built in leveling display
- No maintenance required



3 POINT + QUICK LOCKING TIRE CLAMPS

FAST SETUP with 4 self-centering 3 point tire clamps
- includes quick locking units and ABS claws.

HANDHELD TABLET CONNECTS VIA WIFI

Take the alignment tablet with you as you make assessments, adjustments and collect the necessary data to get the job done from anywhere in the bay.

Always have live readings while making adjustments

A magnet kit is adhered to the back of the tablet allowing positioning directly to the lift or vehicle during the measuring processes.



UPDATED ANIMATED INSTRUCTIONS AND GRAPHICS GUIDE THE ALIGNMENT PROCESS

INCLUDES Spoiler Program for lowered vehicles - measures sport and tuned car bodies.

STANDARD EQUIPMENT

- 1 control unit with PC, 32" monitor, keyboard, printer, mouse and mouse pad
- TABLET for running the Connect APP
- Wi-Fi dongle
- Remote control located on each sensor
- 2 measuring heads
- Extra set of batteries (2)
- 4, STDA35E/3D 3-point clamps with targets
- Set of 6 extensions for dually wheels
- 1 brake pedal depressor
- 1 steering wheel lock
- Instruction manual
- Runs on WINDOWS 10
- Two years free vehicle data updates
- 3-Year Parts Warranty
- 1-Year Labor Warranty

OPTIONAL EQUIPMENT

STDA3D/QC

Kit of two stands for model R1080. For use with the R1080 Sensors as a Quick Alignment Check.



#S130205 Turning Radius Gauge

Single 1.5" tall stainless steel radius gauge
No Pointer / 1-1/2" tall
4,500 lbs. (2,041kg) capacity
(2 required)

#S130237 Turning Radius Gauge

Single 1.5" tall stainless steel radius gauge
No Pointer / 1-11/16" tall
4,500 lbs. (2,041kg) capacity
(2 required)

WS0036

Cordless VIN Scan Tool

Includes charging/communication base, and 4-port USB adapter.



Rotary Wheel Service Equipment

2700 Lanier Drive / Madison, IN 47250, USA

North / South America Information

Sales:

800.445.5438

internsales@vsgdover.com

Tech. Support:

800.445.5438

technicalsupport@rotarylift.com

Global Contact Information

USA: 1.812.273.1622

Canada: 1.905.812.9920

Latin America / Caribbean: 1.812.273.1622

Brazil: +55.11.4534.1995



www.rotarylift.com/Wheel-Service

Government Sales:

800.445.5438 X5655



Contract No. 061015-RRL



FSS Contract No. GS07F2944A



Contract No. 05316

For additional information: rotarylift.com/Government-Purchasing-Assistance/

R1090PRO ADVANTAGES

TOWER FREE SYSTEM

Maximize available workspace.

Don't give up valuable bayspace in your shop.

NO MINIMUM BAY SIZE REQUIRED

No fixed obstacles or obstruction in front of lift.

Portable aligner console can be positioned anywhere for the ultimate convenience.

NO COMPENSATION or ROLL BACK*

No physical rolling or pushing of the vehicle to make runout compensation. Automatic and instant 3D target visualization.

*FOR MOST VEHICLES

NO INTERRUPTIONS

Perfect transmission signals. Always.

NO LIMITATIONS

Can be used at any height!

No need to dedicate bays for alignment service only.

Use the aligner in more than one bay location with optional sensor supports.

TOTAL MEASURING RANGE / R1090

TECHNICAL DATA	MEASURING RANGE	TOTAL RANGE
FRONT AXLE		
Total toe	+/- 2'	+/- 2°
Partial toe	+/- 1'	+/- 1°
Set-back	+/- 2'	+/- 2°
Camber	+/- 2'	+/- 3°
Caster	+/- 5'	+/- 10°
King pin	+/- 5'	+/- 10°
REAR AXLE		
Total toe	+/- 2'	+/- 2°
Partial toe	+/- 1'	+/- 1°
Set-back	+/- 2'	+/- 2°
Camber	+/- 2'	+/- 3°
Thrust angle	+/- 2'	+/- 2°
Power supply	110v / 10 / 60 Hz	



SCAN CODE FOR
PRODUCT VIDEO

Lit# **Rotary R1090 Aligner Cutsheet.2021.11**

©2021 VEHICLE SERVICE GROUP™. Printed in U.S.A. All Rights Reserved.
Unless otherwise indicated, ROTARY, VEHICLE SERVICE GROUP™, DOVER and all other trademarks are property of Dover Corporation and its affiliates.

Rotary wheel aligners are manufactured using the following patents:
US Patent No. 9,453,724 B2 / US Patent No. 9,300,864 B2

Product specifications, part numbers, images and component descriptions are subject to change without notice or liability.

ROTARY WHEEL SERVICE EQUIPMENT now carries a 3 year warranty. See website for details.