

R1150 LEVERLESS

TRUE LEVERLESS CHANGER with VARIABLE SPEED CONTROL
No-lever action, hub mounting changer - no tire tools and contact to metal.

Simple to operate, simple to maintain using 2 button EASY CONTROLS

Powerful changer uses a 220v inverter motor, so torque is always available when needed.

0-15 RPM VARIABLE SPEED CONTROL

The motor, which is equipped with an exclusive inverter that regulates rotational speed, offers the operator customizable speed control. Rotational speed slows as the stress on the bead increases, avoiding any damage to the tire.

Service the most challenging tire and wheel combinations

- low profiles, runflats, exotic rims and other specialty jobs.
Change difficult light truck combinations such as 17.5" and 19.5" super duty wheels using optional centering adapter VSG1000A152.

FEATURES

- Quick locking wheel centering adapter
- Locking system suitable for reverse rims
- Full range of bead clamps and adapters



EASY ROLLER BEAD-BREAKING FEATURE

- Bead-breaking in correct position
- Easy rotation of the roller
- Automatic roller side-movement
- Memorized position for bead breaking of lower side



TIRE DEMOUNTING

- The tool enters between bead and rim
- Levering on the rim, the tool pulls up the bead, minimizing tire stress



TIRE MOUNTING


Safe and easy mounting with plastic tool, roller and rotating helper PLUS93

EQUIPPED WITH

- Standard inflator / side bead blaster
- Pneumatic wheel lift
- Double cone
- Reverse protection
- Tire paste lubricant and brush
- Ships with NEMA L6-20P plug

EASY CONTROLS

Pedal operated inflation with gauge and balancing valve. Easy to use position roller with up / down controls.



OPTIONAL ACCESSORIES

VSG1000A158

Universal flange for reverse, and Chrome Clad wheels

VSG1000A123

Plastic/Chrome Clad adapter for clamping wheels through locking holes

VSG1000A102

5 stud kit 110mm long for reverse rims. Used on VSG1000A87

VSG1000A152

Light truck adapter for centering locking tire changer - 19.5" wheels

VSG1000A118

Match mounting roller

VSG1000A135

Side bead breaker

VSG1000A86

Re-positionable side mirror



Like Rotary R1150 Changer Cutsheet.2021.11

©2021 VEHICLE SERVICE GROUP®, Printed in U.S.A., All rights reserved. Unless otherwise indicated, RO / RY, VEHICLE SERVICE GROUP®, DOVER and all other trademarks are property of Dover Corporation and its affiliates.

Product specifications, part numbers, images and component descriptions are subject to change without notice or liability.

ROTARY WHEEL SERVICE EQUIPMENT now carries a 3 year warranty. See website for details.

Site Requirements:
220V / 1Ø / 20 amp power supply / 115-145 psi air supply



SCAN CODE FOR
PRODUCT VIDEO

R1150 LEVERLESS services:



Optional equipment may be required

TECHNICAL DATA	R1150
Handle wheels from*	10"-26" / 12"-28" / 14"-30"
Maximum tire width	15"
Maximum tire diameter	45"
Bead breaker power (each arm)	2,645 Ft/L lbs
Bead breaker movement	Automatic
Rotation motor	2Hp / 1.5 Kw inverter motor
Recommended air supply	115-145 PSI / 8-10 bar
Power supply	220v / 1Ø / 60 Hz

* 3-position base can be adjusted to fit larger wheels up to 30"