
# R148 PRO 2D TECHNOLOGY

# **ELECTRONIC BALANCER with MICROPROCESSOR**

**EOUIPPED WITH AUTO WHEEL DIMENSION CALIPER** PERFECT BALANCING WITH AUTOMATIC MEASUREMENT OF WHEEL DISTANCE AND DIAMETER.

#### **AUTOMATIC LOCK IN POSITION**

Automatic start when the cover is lowered.













Automatic rotation Automatic stop in the external unbalanced position. to the internal side.





# **AUTOMATIC DISTANCE + DIAMETER MEASUREMENT**

Caliper for automatic distance and diameter measurement. Automatic ALU S program.






#### **LARGE DIGITAL DISPLAYS**

12 PROGRAM FEATURES FOR CAR, LIGHT TRUCK AND MOTORCYCLE WHEELS

# STANDARD ACCESSORIES OPTIONAL ACCESSORIES SEE NEXT PAGE





- Clad Wheel Problem Solver
- Static Imbalance Solution
- Lower Taper For Better Mounting
- No Wheel Hub Interference







**GAR 112 Light truck cone** 3.75"- 5" (95-124 mm)



**GAR 345** Large quick nut replacement lock







Wheel diameter: 10" - 30" Tire width: 1.5" - 22"

Maximum tire diameter: 44"









#### Optional equipment may be required

# DIMENSIONS:

HEIGHT: 52" / 66.5" with hood up WIDTH: 46.625" DEPTH: 37"

TECHNICAL DATA	R148
Max. assembly weight	154 lbs. (70kg)
Read out accuracy	1 g
Cycle time	6 seconds
Rotation speed (rpm)	<100
Power supply	110v / 60 Hz / 1Ø