


AUTOMATIC LOCK IN POSITION

Automatic start when the cover is lowered.

DEMANDING PROFESSIONALS







Automatic rotation to the internal side.



Automatic stop in the internal unbalanced position.

EASY OPERATION

Interactive inputs guide tech during all phases of the balancing process.



Automatic storage of distance and diameter.

INTERNAL DATA ARM



Automatic programs.

(ED KEYBOARD

R155.



MONITOR KEYBOARD

Linked directly to a standard monitor, this durable touch-pad allows for a "gloved" input with the convenience of a touch screen monitor.



with internal data gauge.

The laser pointer indicates the exact positioning for weights



DOUBLE LED



PRODUCT VIDEO



WIDTH GAUGE



3D wheel tire sensor caliper for automatic measure of rim width



Wheel diameter: 10" - 30 Tire width: 1.5" - 22" Maximum tire diameter: 44"

R155 PRO 3D services:







DIMENSIONS:

HEIGHT: 57.625" / 66.5" with hood up WIDTH: 50.25" DEPTH: 37.75"

TECHNICAL DATA	R155
Max. assembly weight	154 lbs. (70kg)
Read out accuracy	1 g
Cycle time	6 seconds
Rotation speed (rpm)	<100
Power supply	110v / 60 Hz / 1Ø

STANDARD ACCESSORIES OPTIONAL ACCESSORIES SEE PAGE 5



HW150400132 / 2.07"- 4.35" (52.5-110.7mm) Seven-piece Pro Collet Kit 40mm

Quick selection and rim run-out measurement

- · Clad Wheel Problem Solver
- Static Imbalance Solution
- · Lower Taper For Better Mounting
- · No Wheel Hub Interference



QUICK LOCK





GAR 112 Light truck cone 3.75"- 5" (95-124 mm)